floors@home

PROJECT FLOORS

Technical Data

	floors@home/40	floors@home/30	floors@home/20
Covering type according to EN 649	Heterogeneous Plankwood / Tiles	Heterogeneous Plankwood / Tiles	Heterogeneous Plankwood / Tiles
Number of colours	16 planks / 4 tiles	74 planks / 31 tiles	24 planks / 6 tiles
Packaging per box/pallet	3.34 m²/240.48 m²	3.34 m²/240.48 m²	3.34 m²/240.48 m²
Performance classification EN 685	23, 32, 41	21-23, 31	22
Total thickness EN 428	2.0 mm	2.0 mm	2.0 mm
Wearlayer thickness EN 429	0.4 mm	0.3 mm	0.2 mm
Surface treatment	Yes/PU	Yes/PU	Yes/PU
Bevelled edges	Yes/Depending on design	Yes/Depending on design	No
Total weight EN 430	3.47 kg/m²	3.8 kg/m²	3.1 kg/m²
Residual indentation EN 433	0.05 mm	0.05 mm	0.05 mm
Castor chair suitability EN 425	yes – using EN 12529, Typ W	yes – using EN 12529, Typ W	yes – using EN 12529, Typ W
Underfloor heating	suitable up to 28 °C	suitable up to 28 °C	suitable up to 28 °C
Behaviour to fire EN 13501-1	Bfl-s1	Bfl-s1	Bfl-s1
Resistance to thermal conductivity ISO 8302	0.02 m² K/W	0.02 m² K/W	0.02 m² K/W
Impact sound improvement ISO 10140	2dB	2dB	2dB
Colour fastness EN 20105-B02/2	> 6	> 6	> 6
Electrostatic characteristics EN 1081	> 10^{10}	> 10^{10}	> 10^{10}
Chemical resistance EN 423	conforms*	conforms *	conforms *
Slip resistence	R9	R9	R9
Adhesive recommendation	see installation instruction	see installation instruction	see installation instruction
Maintenance/Cleaning recommendation	CC-Dr. Schutz	CC-Dr. Schutz	CC-Dr. Schutz

* Vis-à-vis the short-term effects of normal, domestic agents.

Please also note the installation and cleaning and care instructions.

(Date: 01/01/2015)

PROJECT FLOORS GmbH ◦ Max-Ernst-Str. 4 ◦ D-50354 Hürth
Telefon +49 (0) 2233 9687-0 ◦ Fax +49 (0) 2233 9687-10 ◦ www.project-floors.com ◦ info@project-floors.com